



DiZeit Time Switches / Timelite DBs

Save Energy For A Better Tomorrow

DiZeit Analog Time Switch



Cat Ref. TA916422

- Degree of protection : IP 20
- Din channel mounting, single module analog time switch with power reserve facility
- 24 hours programme, quartz control motor drive
- Voltage : 230V AC , 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Switching Capacity at $\text{Cos}\phi = 0.6$, 250V : 10A
- Power Reserve : 100 hours
- Switching Step : 15 minutes
- Minimum Switching Time : 15 minutes
- Time Accuracy : ± 2.5 seconds/day
- Contact Type : 1 CO contact SPDT
- Ambient Temperature : -10° to $+55^\circ$ C
- Approx Weight : 67g



Cat Ref. TA926453

- Degree of protection : IP 20
- Din channel mounting, three module analog time switch with power reserve facility
- 24 hours programme, quartz control motor drive
- Voltage : 230V AC , 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Switching Capacity at $\text{Cos}\phi = 0.6$, 250V : 10A
- Power Reserve : 100 hours
- Switching Step : 15 minutes
- Minimum Switching Time : 30 minutes
- Time Accuracy : ± 2.5 seconds/day
- Contact Type : 1 CO contact SPDT
- Ambient Temperature : -10° to $+55^\circ$ C
- Approx Weight : 150g
- TA925450 is available without power reserve



Cat Ref. TA912472

- Degree of protection : IP 30
- Front mounting, analog time switch with power reserve facility
- 24 hours programme, quartz control motor drive
- Voltage : 230V AC , 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Switching Capacity at $\text{Cos}\phi = 0.6$, 250V : 8A
- Power Reserve : 100 hours
- Switching Step : 10 minutes
- Minimum Switching Time : 20 minutes
- Time Accuracy : ± 2.5 seconds/day
- Contact Type : 1 CO contact SPDT
- Ambient Temperature : -10° to $+55^\circ$ C
- Approx Weight : 100g
- TA912473 is available without power reserve



DiZeit Analog Time Switch

Cat Ref. TA926129

- Degree of protection : IP 20
- Din channel mounting, weekly three module analog time switch with power reserve facility
- 7 days programme, quartz control motor drive
- Voltage : 230V AC, 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Switching Capacity at $\text{Cos}\phi = 0.6$, 250V : 10A
- Power Reserve : 100 hours
- Switching Step : 2 hours
- Minimum Switching Time : 4 hours
- Time Accuracy : ± 2.5 seconds/day
- Contact Type : 1 CO contact SPDT
- Ambient Temperature : -10° to $+55^\circ$ C
- Approx Weight : 150g



DiZeit Digital Time Switch

Cat Ref. TDA41110

- Din channel mounting, annual digital time switch
- Voltage : 230V AC , 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Switching Capacity at $\text{Cos}\phi = 0.6$, 250V : 4A
- Battery Reserve : 6 years
- No. of Programmes : 2 channel x 3 programme type x 28 programme
- Geographical Coordinates : Resolution 1 degree
- Time Accuracy : ± 1 seconds/day
- Contact Type : 2 CO contact SPDT
- Ambient Temperature : -10° to $+55^\circ$ C



Cat Ref. TDA43110

- Din channel mounting, daily/weekly two module digital time switch
- Voltage : 230V AC , 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Battery Reserve : 6 years
- Minimum Switching Time : 1 minute
- Time Accuracy : ± 1 seconds/day
- Contact Type : 1 Change Over contact SPDT
- No. of Programmes : 28
- Ambient Temperature : -10° to $+55^\circ$ C
- TDA43111 is available with 2 CO contact and 14 programmes per channel

DiZeit Digital Time Switch



Cat Ref. TDA45194

- Degree of protection : IP 20
- Din channel mounting, two module astronomical light sensitive digital time switch
- Voltage : 230V AC , 50/60Hz
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Switching Capacity at $\text{Cos}\phi = 0.6$, 250V : 4A
- Battery Reserve : 6 years
- No. of Programmes : 28
- Geographical Coordinates : Resolution 1 degree
- Switching Step : 1 Minute
- Minimum Switching Time : 1 minute
- Time Accuracy : ± 1 seconds/day
- Contact Type : 1 CO contact SPDT
- Ambient Temperature : -10° to $+55^{\circ}$ C
- Approx Weight : 284g
- TDA45193 Din mounted Astronomical Digital time switch is available with 2 CO contact



Cat Ref. TSA58107

- Degree of protection : IP 30
- Din channel mounting, single module light sensitive switch
- Voltage : 230V AC , 50/60Hz
- With outer sensor
- Sensing distance < 50 meters
- Switching Capacity at $\text{Cos}\phi = 1$, 250V : 16A
- Control from 100 Lux to 100 kLux
- Contact Type : 1 CO contact SPDT
- Ambient Temperature : -40° to $+60^{\circ}$ C

DiZeit Timelite Distribution Boards

Electricity is exponentially taking over our life style. Its consumption in our life has gone up many folds. Its usage has gone up neck pace in various applications like domestic or industrial. This has necessitated to utilize electrical energy in safe, efficient way so that it continues to play a pivotal role in our life. This requires a design / solution which can protect from overload / short circuit with addition to save energy in every possible way. Timelite a prefabricated & engineered solution protection & energy saving for lighting applications.



Salient Features

- Degree of Protection : IP 54
- Aesthetically appealing with locking facility
- Switch-ON & Switch-OFF street lights on time scheduling basis by incorporating a analog/digital time switch and contactor
- Rating of contactors depends on the luminaires and wattage of lighting loads
- Range includes from 16A to 110A with analog/digital time switch. Model incorporating energy meter is also available on request
- Selector switch for selecting time mode, continuous ON mode or permanent OFF mode



Rating (A)	MCB* (Ratings)	MCCB** (Ratings)	Time Switch		Contactor*** (AC-3 Rating)
			Analog	Digital	
16A	16A	-	TA926453	TDA43110	16A
32A	32A	-	TA926453	TDA43110	32A
40A	40A	-	TA926453	TDA43110	40A
50A	50A	-	TA926453	TDA43110	50A
65A	-	80A	TA926453	TDA43110	65A
80A	-	80A	TA926453	TDA43110	80A
95A	-	100A	TA926453	TDA43110	95A
110A	-	125A	TA926453	TDA43110	110A

*MCB will be of 'C' curve 10kA breaking capacity.

**Standard MCCB will have 16kA breaking capacity.

***Contactor coil voltage is 230V AC as standard.

CORPORATE OFFICE: B-24, Phase - II, Noida - 201305, U.P., India Ph.: +91-120-3853000 Fax: +91-120-3853002 E-mail: sales@indoasian.com, international@indoasian.com Website: www.indoasian.com

CONSUMER CARE CELL: B-24, Phase - II, Noida - 201305, U.P., India Ph.: +91-120-3042222 E-mail: feedback@indoasian.com

NORTH

CHANDIGARH

S.C.O.-11, 2nd Floor,
Madhya Marg, Sector-26,
Chandigarh-160002
Ph.: 0172-3934651-64
Telefax: 0172-3934656
E-Mail: in-chandigarh-office@indoasian.com

DELHI

721-722, 7th Floor,
DLF Tower B,
Jasola District Centre,
New Delhi-110044
Ph.: 011-30821773-74
E-Mail: in-delhi-office@indoasian.com

JAIPUR

433, Ganpati Plaza,
M. I. Road,
Jaipur-302001
Ph.: 0141-4113528
E-Mail: in-jaipur-office@indoasian.com

LUCKNOW

301, Chintel House,
Station Road,
Lucknow-226001
Ph.: 0522-4013210
TeleFax: 0522-4013210
E-Mail: in-lucknow-office@indoasian.com

SOUTH

BANGALORE

402, 4th Floor, Blue Cross Chambers,
Infantry Road Cross,
Bangalore-560001
Ph.: 080-25585043, 25591677
Fax: 080-25591546
E-Mail: in-bangalore-office@indoasian.com

COCHIN

35/1403 B, 1st Floor,
M. K. M. Building, Palarivattom,
Cochin-682025
Ph.: 0484-4055581-88
Fax: 0484-4055589
E-Mail: in-cochin-office@indoasian.com

COIMBATORE

D. No. 83,
Dr. Nanjappa Road,
Coimbatore-641018
Ph.: 0422-2302715
Fax: 0422-2302715
E-Mail: in-coimbatore-office@indoasian.com

CHENNAI

Ambal Building,
1st Floor, 727,
Anna Salai,
Chennai-600006
Ph.: 044-28297527, 28297143
E-Mail: in-chennai-office@indoasian.com

HYDERABAD

312, 3rd Floor,
Amrutha Estates,
Himayath Nagar,
Hyderabad-500029
Ph.: 040-66742425-29
E-Mail: in-secunderabad-office@indoasian.com

WEST

AHMEDABAD

203-204, Shreedhar Avenue,
11, Sardar Patel Colony,
Near Sardar Patel Statue,
Naranpura, Ahmedabad-380014
Ph.: 079-30002092-94
Fax: 079-27680439
E-Mail: in-ahmedabad-office@indoasian.com

GOA

No. 606, 6th Floor,
Unitech City Center,
M.G. Road, Panjim,
Goa-403501
Ph.: 0832-2420934, 9422445501
E-Mail: in-go-a-office@indoasian.com

INDORE

C-18, Block B,
New Siyaganj Market,
Indore-452007
Ph.: 0731-4064064, 8889211108
Fax: 0731-4064064
E-Mail: in-indore-office@indoasian.com

MUMBAI

G-6, Nahar & Seth Industrial Estate,
Chakala, Andheri East,
Mumbai-400099
Ph.: 022-28390072, 28301987
Fax: 022-66922831
E-Mail: in-mumbai-office@indoasian.com

PUNE

Rajadwar Building, 4th Floor,
1307, Shivaji Nagar,
Off. J. M. Road,
Pune-411005
Ph.: 020-30116638-39, 60501144
Fax: 020-25520659
E-Mail: in-pune-office@indoasian.com

EAST

SURAT

306, Golden Point,
Ring Road,
Surat-395003
Ph.: 0261-3990890, 9825224054
E-Mail: in-surat-office@indoasian.com

JAMSHEDPUR

9, Rustomji Mansion
Main Road, Near Signal Light,
Bistupur, Jamshedpur-831001
Ph.: 09830893435
E-Mail: in-jamshedpur-office@indoasian.com

KOLKATA

61/B, Palm Avenue,
Kolkata-700019
Ph.: 033-32934121, 32609475
E-Mail: in-kolkata-office@indoasian.com